



Lift capacities calculated at attachment pivot point on stick (lbs).  
No attachment on stick. Attachment weight must be subtracted.  
Heavy lift on.

REACH														HEIGHT	
40'		35'		30'		25'		20'		15'		10'			
Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	Front		
														35'	
		* 14,183	* 14,183											30'	
		* 18,471	* 18,471											25'	
		* 20,959	* 20,959	* 22,995	* 22,995									20'	
* 16,518	* 16,518	21,419	* 23,663	* 26,713	* 26,713									15'	
16,931	* 18,830	20,795	* 26,630	26,132	* 29,508	* 33,872	* 33,872	* 41,089	* 41,089	* 54,943	* 54,943			10'	
16,582	* 20,139	20,172	* 28,066	25,126	* 31,879	32,428	* 37,670	44,336	* 47,357	* 61,130	* 61,130			5'	
16,294	* 19,631	19,637	27,698	24,275	* 33,784	31,108	* 40,617	42,265	* 51,738	* 45,866	* 45,866			0'	
		19,265	27,297	23,671	33,911	30,220	* 42,277	41,049	* 53,796	* 48,580	* 48,580	* 26,548	* 26,548	-5'	
		19,124	27,146	23,363	33,574	29,776	* 42,371	40,542	* 53,546	* 57,985	* 57,985	* 36,166	* 36,166	-10'	
				23,397	* 32,977	29,761	* 40,550	40,608	* 50,905	63,036	* 66,559	* 48,117	* 48,117	-15'	
				23,909	* 28,016	30,209	* 36,015	41,209	* 45,318	* 58,252	* 58,252	* 63,932	* 63,932	-20'	
						* 26,033	* 26,033	* 35,053	* 35,053	* 44,847	* 44,847			-25'	
														-30'	
														-35'	
														-40'	

**Notes:**

1. Do not attempt to lift or hold any load that exceeds these rated values at their specified load radii and heights.
2. The least stable position is over the side.
3. The operator should be fully acquainted with machine operation before operating the machine.
4. Lifting capacities assume a machine standing on level, firm and uniform supporting surface. Operator must make allowance for job conditions such as soft or uneven ground, out of level conditions, side loads, sudden stopping of loads, hazardous conditions, inexperienced personnel, etc.
5. The above theoretical ratings are based on calculations derived from standard O.E.M. lift charts. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping capacity. Rated loads marked with an asterisk (\*) are limited by hydraulic lifting capacity.